

## ACIQ - Heat pump water heater : ACIQ-50G-HP-WH

PerformantSecond Second Se	Specifications	
ENERGY STAR Partner:INVAC Energy, LLCBrand Name:ACIQModel Name:Heat pump water heaterModel Number:ACIQ-50G-HP-WHConnected Capable:YesConnects Using:Wi-FI, CTA-2045-DR Protocol:A - Built-inCommunication Hardware Architecture:A - Built-inTax Credit Eligible:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Ampe:44.0Untug of HPW H(V):24.0Draw Pattern (Intended Usage):Hedium-UsageFirst Hour Rating (gallons):69Heat Pump Type:24.0 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):77.4Niform Energy Factor (UEF):3.75Refrigerant with GWP:5.5Electric Input (kW):5.5Electrol Usage (kWh/yr):55.0Storage Volum (gallons):65.0Electric Input (kW):65.0Arto-Querce (gallons):65.0Storage Volum (gallons):65.0Storage Volum (gallons):65.0Storage Volum (gallons):65.0Bits Hour Rating (gallons):65.0Bits Hour Rating (gallons):65.0Storage Volum (gallons):65.0Storage Volum (gallons):67.0Bits Hour Rating (gallons):67.0Bits Hour Rating (gallons):67.0Bits Hour Rating (gallons):67.0Bits Hour Rating (gallo		2626954
Brand Name:ACIQModel Name:Heat pump water heaterModel Number:ACIQ-50G-HP-WHConnected Capable:YesConnects Using:Wi-FI,CTA-2045-DR Protocol:CTA-2045-BCommunication Hardware Architecture:A - Built-inTime Of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:440Input Voltage for HPWH (V):240Pattern (Intended Usage):Heidum-UsageFirst Hour Rating (gallons):69Heat Pump Type:204 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (F):37.5Referent with GWP:3.75Recover Efficiency %):35.0Electric Input (KW):5.5Electric Usage (KWhyr):85.0Recover Efficiency %):85.0Artone Compressor Cut Off Temperature for HPWH (F):3.70Refore Stage (KWhyr):85.0Recover Efficiency %):85.0Artone Compressor Cut Off Temperature for HPWH (F):3.70Recover Efficiency %):85.0Recover Efficiency %):85.0Recover Efficiency %):85.0Retrieu Tup Lagae (KWhyr):85.0Rora Volume (gallons):7.0Tank Diameter (inches):7.0Rora Volume (gallons):87.0Rora Volume (gallons):87.0Rora Volume (gallons):87.0Rora Volum		
Model Name:Heat pump water heaterModel Number:ACIQ-50G-HP-WHConnected Capable:YesConnects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A - Built-inTime of Use Schedule:YesTax Credit Eligible:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:240Input Voltage for HPWH (V):240Darw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Nufferant with GWP:No.6Refigerant with GWP:3.75Recover Efficiency (%):35.0Electric Usage (kWhyr):85.0Storage Volume (gallons):47.0AnaloStorage Volume (gallons):Arxing Carlons (construction):18.3AnaloAnolStorage Volume (gallons):47.9Storage Volume (gallons):85.0Storage Volume (gallons):18.3Analos47.9Storage Volume (gallons):47.9Storage Volume (gallons):87.9Storage Volume (gallons):87.9Storage Volume (gallons):87.9Storage Volume (gallons):87.9Storage Volume (gallons):87.9Storage Volume (gallons):87.9<		
Model Number:ACIQ-50G-HP-WHConnectel Capable:YesConnects Using:Wi-Fi,CTA-2045-BDR Protocol:A Built-inCommunication Hardware Architecture:A Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Amps:24.0Input Voltage for HPWH (V):240Pattern (Intended Usage):Heilum-UsageFirst Hour Rating (gallons):69Lower Compressor Cut Off Temperature for HPWH (F):7.4Difform Energy Factor (UEF):3.74Refrigerant with GWP:S.5Energy Fifteioury (%):3.5Electric Usage (kMhyr):5.5Electric Usage (kMhyr):8.3Ana Dameer (inches):18.3Ana Pattern (inches):8.3Ana Patter		
Connected Capable:YesConnects Using:Wi-Fi,CTA-2045-BDR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Hedium-UsageFirst Hour Rating (galons):69Lower Compressor Cut Off Temperature for HPWH (*F):37.4Unform Energy Factor (UEF):3.75Recoverg Efficiency (%):43.0.0Electric Usage (kWh/yr):5.5Electric Usage (kWh/yr):5.5Electric Usage (kWh/yr):8.5.0.0Tana Diametr (inches):18.3Tana Patter (inches):18.3Tana Patter (inches):24.0.1Tana Patter (inches):24.0.2Tana Patter (inches):25.0Tana Patter (inches):25.0Tana Patter (inches):24.0.2Tana Patter (inches):24.0.2Tana Patter (inches):24.0.2Tana Patter (inches):24.0.2Tana Patter (inches):25.0Tana Patter (inches):24.0.2 <t< th=""><th></th><th></th></t<>		
Connects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:VesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Arnps:24.0Input Voltage for HPWH (V):240Pare Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH ("F):37.4Starge Totune (Temperature for HPWH ("F):37.5Refrigerant with GWP:5.5Electric Input (kW):5.5Electric Input (kW):5.5Storage Volume (gallons):47.0Atomater (inches):47.9Tank Diameter (inches):5.3Tank Height (inches):202411-11		
DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:VesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):3.75Refrigerant with GWP:430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Ana Diameter (inches):18.3Tank Diameter (inches):47.9Date Certified:202411-11	-	
Communication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:Hybrid/Electric Heat PumpType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):VesStarter (Intended Usage):Hedium-UsageFirst Hour Rating (gallons):69Heat Pump Type:24.0 Volt Integrated HPWHLower Compressor Cut Off Temperature for WHY (*F):37.4Upford Energy Factor (UEF):3.75Refigerant with GWP:5.5Electric Input (KW):5.5Electric Usage (kWh/ty):85.0Storage Volume (gallons):17.0Ana Diameter (inches):18.3Tak Diameter (inches):18.3Tak Height (inches):20.2Storage Volume (gallons):18.3Architecture:18.3Tack Diameter (inches):10.2Storage Volume (gallons):18.3Architecture:18.3Tack Diameter (inches):19.4Storage Volume (gallons):19.4Storage Volume (gallons):10.4Storage Volume (gallons):10.4Architecture:10.4Storage Volume (gallons):10.4Architecture:10.4Storage Volume (gallons):10.4Architecture:10.4Storage Volume (gallons):10.4Architecture:10.4Architecture:10.4Storage Volume (gallons	-	
Time of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for PWH (*F):7.4Upper Compressor Cut Off Temperature for PWH (*F):3.75Refrigerant with GWP:3.75Recovery Efficiency (%):5.5Electric Input (KW):5.5Electric Usage (kWh/yr):85.0Storage Volume (gallons):40.0Tax Diameter (inches):18.3Tax Height (inches):18.3Tax Height (inches):20.2Yes20.		
Tax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Oraw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHVower Compressor Cut Off Temperature for HWWH (*F):7.4Drage Tomperature for WWW (*F):7.4Refrigeran with GWP:8.134a (GWP:1430)Refrigeran with GWP:5.5Electric Input (kW):5.5Electric Usage (kWh/yr):83.0Storage Volume (gallons):8.3Tak Diameter (inches):8.3Tak Diameter (inches):8.3Diameter (inches):8.3Diame		
ENERGY STA Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Strage Tompressor Cut Off Temperature for HPWH (*F):91.4Num Compressor Cut Off Temperature for HPWH (*F):91.4Refrigeran with GWP:R.134a (GWP:1430)Recovery Efficiency (%):3.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):41.0Tank Diameter (inches):18.3Tank Height (inches):30.2Date Certified:20241111		
Type:Hybrid/Electric Heat PumpFue:ElectricMax. Amps:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):7.4Dyper Compressor Cut Off Temperature for HPWH (°F):8.134a (GWP:1430)Refrigerant with GWP:8.134a (GWP:1430)Inform Energy Factor (UEF):3.5Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):4.7.0Tank Diameter (inches):18.3Date Certified:2024-11.1	-	
Fuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:8-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Usage (kWh/yr):55.5Electric Usage (kWh/yr):18.3Tank Diameter (inches):18.3Tank Height (inches):2024-11-11		
Max. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Dyper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:R-134a (GWP:1430)Recovery Efficiency (%):3.75Electric Input (kW):5.5Electric Usage (kMh/yr):855.0Storage Volume (gallons):4.0Tank Height (inches):4.9Date Certified:3.75		
Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Date Certified:024-11-11		
Draw Pattern (Intended Usage):Medium-UsageFirst Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Cut Different with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Date Certified:2024:11:11		
First Hour Rating (gallons):69Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):18.3Tank Diameter (inches):18.3Date Certified:2024-11-11		
Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):2024-11-11		
Lower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):2024-11-11		
HPWH (°F):Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):2024-11-11		
HPWH (°F):RRefrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11		37.4
Uniform Energy Factor (UEF):3.75Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11		107.6
Recovery Efficiency (%):430.0Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11	Refrigerant with GWP:	R-134a (GWP:1430)
Electric Input (kW):5.5Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11	Uniform Energy Factor (UEF):	3.75
Electric Usage (kWh/yr):855.0Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11	Recovery Efficiency (%):	430.0
Storage Volume (gallons):47.0Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11	Electric Input (kW):	5.5
Tank Diameter (inches):18.3Tank Height (inches):47.9Date Certified:2024-11-11	Electric Usage (kWh/yr):	855.0
Tank Height (inches):47.9Date Certified:2024-11-11	Storage Volume (gallons):	47.0
Date Certified: 2024-11-11	Tank Diameter (inches):	18.3
	Tank Height (inches):	47.9
Markets: United States, Canada	Date Certified:	2024-11-11
	Markets:	United States, Canada

05/02/2025