

CyberPower - CP1500PFCLCDa: CP1500PFCLCDa

Specifications	
ENERGY STAR Unique ID:	2341720
Brand Name:	CyberPower
Model Name:	CP1500PFCLCDa
Model Number:	CP1500PFCLCDa
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	CP1350PFCLCDa
Active Output Power Rating Minimum Configuration (W):	880
Apparent Output Power Rating Minimum Configuration (VA):	1350
Maximum Configuration Tested Model Number:	CP1500PFCLCDa
Active Output Power Rating Maximum Configuration (W):	1000
Topology (ac):	Passive Standby
Topology and Product Type Combined:	Alternating Current (ac) - Offline (VFD)
Application:	Consumer,Commercial
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	60-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	60-60
Rack Mountable:	No
Height (mm):	280
Width (mm):	100
Depth (mm):	354
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage Independent
Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60

Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.56
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.2
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.8
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.9
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.8
Weighted Efficiency Calc Min Config Lowest Dependency:	98.8
Total Input Power in W at 0% Load Max Config Lowest Dependency (ac):	2.66
Efficiency at 25% Load Max Config Lowest Dependency (ac):	98.8
Efficiency at 50% Load Max Config Lowest Dependency (ac):	99.0
Efficiency at 75% Load Max Config Lowest Dependency (ac):	99.0
Efficiency at 100% Load Max Config Lowest Dependency (ac):	99.0
Weighted Efficiency Calc Max Config Lowest Dependency:	99.0
Efficiency (%):	98.8
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	2
Energy Storage System Runtime at 50% Load (min.):	9
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	HTTP,HTTPS,Other,SNMP (v1, 2 or 3)
Communication Protocol Other:	HID, CyberPower serial Protocol (v2)
Manufacturer Take Back Program:	No
Model Web Page URL:	No (Not yet available)
Test Method Guidelines:	N/A
Date Available on Market:	2019-07-31
Date Certified:	2019-07-28
Markets:	United States, Taiwan, Japan, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

CP1350PFCLCDa,CP1350PFCLCDa;; CP1460PFCLCDa,CP1460PFCLCDa;; CST1350SUC,CST1350SUC,; CST1460SUC,CST1460SUC,; CST1500SUC,CST1500SUC,; GX1500U,GX1500U,

Captured On: 04/25/2025