

Tripp Lite - AG-0305 : INTERNET350U

ENERGY STAR Unique ID: 2384213 Brand Name: Tripp Lite Model Name: AG-0305 Model Number: INTERNET350U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0305 Active Output Power Rating Minimum Configuration (W): AG-0305 Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Possive Standby Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): 185-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): No Rated Output Voltage (V): No Height (mm): 105 Width (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: AUM Output State Output Stat	Specifications	
Brand Name: Tripp Lite Model Name: AG-0305 Model Number: INTERNET350U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: 210 Active Output Power Rating Minimum Configuration (W): 350 Apparent Output Power Rating Minimum Configuration (W): Passive Standby Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: No Nomand Mode(s) Input Dependency Voltage and Frequency Dependent Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V rms): 120	•	
Model Name: AG-0305 Model Number: INTERNET350U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0305 Active Output Power Rating Minimum Configuration (W): 350 Apparent Output Power Rating Minimum Configuration (WA): 350 Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 105 Rack Mountable: No Height (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 <th< th=""><th>•</th><th></th></th<>	•	
Model Number: INTERNET35UU Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): 185-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rated Output Frequency (Hz): No Height (mm): 105 Width (mm): 110 Depth (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: No Normal Mode(s) Input Dependency Characteristic (ac): No Nouther of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		1 1
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-0305 Active Output Power Rating Minimum Configuration (W): 210 Apparent Output Power Rating Minimum Configuration (VA): 350 Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge 3 Protected Outlets: No Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Freq		
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Frequency (Hz): Robert (mm): Robe	Model Number:	INTERNET350U
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): So-60 Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rock Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120 Test Input Frequency (Hz): 120	_	AG-0305
Configuration (VA): Topology (ac): Passive Standby Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer, Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: No Height (mm): Hight (mm): Hight (mm): Hight (mm): Hight of Surge Protected Only Outlets: No Nomal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V): Hight (VA): Frequency (Hz): Frequency (Hz)		210
Topology and Product Type Combined: Alternating Current (ac) - Offline (VFD) Application: Consumer,Commercial Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120		350
Application: Consumer,Commercial Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology (ac):	Passive Standby
Rated Input Voltage (V rms): 185-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Dependent Number of Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Topology and Product Type Combined:	Alternating Current (ac) - Offline (VFD)
Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Application:	Consumer,Commercial
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Voltage (V rms):	185-120
Rated Output Frequency (Hz): 50-60 Rack Mountable: No Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Normal Modes Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Frequency (Hz):	50-60
Rack Mountable: Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Voltage (V): 120 Test Output Voltage (V): 110 110 110 110 110 110 110 1	Rated Output Voltage (V):	120-120
Height (mm): 105 Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: No No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Frequency (Hz):	50-60
Width (mm): 110 Depth (mm): 185 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Number of Surge Protected Only Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rack Mountable:	No
Depth (mm): Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 3 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Height (mm):	105
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Width (mm):	110
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Depth (mm):	185
Protected Outlets:Number of Surge Protected Only Outlets:3Normal Mode(s) Input Dependency Characteristic (ac):Voltage and Frequency DependentModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage and Frequency DependentTest Input Voltage (V rms):120Test Input Frequency (Hz):60Test Output Voltage (V):120	Total Number of Outlets:	6
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Dependent Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		3
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Surge Protected Only Outlets:	3
Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Dependent 120 Test Input Voltage (V rms): 60 Test Output Voltage (V): 120		Voltage and Frequency Dependent
Default Normal Mode (ac): Voltage and Frequency Dependent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Default Normal Mode (ac):	Voltage and Frequency Dependent
Test Output Voltage (V): 120	Test Input Voltage (V rms):	120
	Test Input Frequency (Hz):	60
Test Output Frequency (Hz): 60	Test Output Voltage (V):	120
	Test Output Frequency (Hz):	60

Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	2.11
Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.3
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.1
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.2
Weighted Efficiency Calc Min Config Lowest Dependency:	98.7
Efficiency (%):	98.7
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	2
Energy Storage System Runtime at 50% Load (min.):	7
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Battery Recycling URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available:	Other,USB Port
Communication Protocols:	None
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Model Web Page URL:	https://www.tripplite.com/internet-office-120v-350va-180w-standby-ups-ultra-compact-desktop-usb~internet350u
Test Method Guidelines:	N/A
Date Available on Market:	2019-10-08
Date Certified:	2021-09-07
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Additional Model Information

AG-0307,INTERNET350SER,; AG-87AF,BC350U,

Captured On: 04/24/2025