

Tripp Lite - AG-06B4 : SMART1500TSU

| Specifications | |
|--|--------------------------|
| ENERGY STAR Unique ID: | 2395396 |
| Brand Name: | Tripp Lite |
| Model Name: | AG-06B4 |
| Model Number: | SMART1500TSU |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | AG-06B4 |
| Active Output Power Rating Minimum Configuration (W): | 1200 |
| Apparent Output Power Rating Minimum Configuration (VA): | 1440 |
| Topology (ac): | Line Interactive |
| Topology and Product Type Combined: | ac Line Interactive (VI) |
| Application: | Consumer,Commercial |
| Rated Input Voltage (V rms): | 381-120 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 120-120 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | No |
| Height (mm): | 191 |
| Width (mm): | 140 |
| Depth (mm): | 381 |
| Total Number of Outlets: | 8 |
| Number of Battery Backup and Surge Protected Outlets: | 6 |
| Number of Surge Protected Only Outlets: | 2 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage Independent |
| Test Input Voltage (V rms): | 120 |
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 120 |
| Test Output Frequency (Hz): | 60 |

| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): Efficiency at 25% Load Min Config Lowest Dependency (ac): Efficiency at 50% Load Min Config Lowest Dependency (ac): Efficiency at 75% Load Min Config Lowest Dependency (ac): 98.9 |
|---|
| Dependency (ac): Efficiency at 50% Load Min Config Lowest Dependency (ac): Efficiency at 75% Load Min Config Lowest 98.9 |
| Dependency (ac): Efficiency at 75% Load Min Config Lowest 98.4 |
| |
| |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): 98.4 |
| Weighted Efficiency Calc Min Config Lowest Dependency: 98.6 |
| Efficiency (%): 98.6 |
| Modular UPS Module Tested Model Number: N/A |
| Energy Storage Mechanism: Battery |
| Energy Storage System Technology: Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: Integral |
| Energy Storage System Removable to Another No Room: |
| Energy Storage System Runtime at 100% Load 4 (min.): |
| Energy Storage System Runtime at 50% Load (min.): |
| Energy Storage System Warranty (yrs): 3 |
| Energy Storage System Information URL: N/A |
| Battery Recycling URL: http://www.tripplite.com/en/support/recycling-program.cfm |
| Network Connections Available: Serial Port,USB Port,Ethernet |
| Communication Protocols: None |
| Manufacturer Take Back Program: Yes |
| Manufacturer Take Back Program URL: http://www.tripplite.com/en/support/recycling-program.cfm |
| |
| Model Web Page URL: https://www.tripplite.com/1440va-1200w-line-interactive-ups-8-nema-5-15r-outlets-avr-120v-50-60hz-usb-lcd-tower~smart1500tsu |
| |
| nema-5-15r-outlets-avr-120v-50-60hz-usb-lcd-tower~smart1500tsu |
| nema-5-15r-outlets-avr-120v-50-60hz-usb-lcd-tower~smart1500tsu Test Method Guidelines: N/A |
| nema-5-15r-outlets-avr-120v-50-60hz-usb-lcd-tower~smart1500tsu Test Method Guidelines: N/A Date Available on Market: 2021-12-31 |

Captured On: 04/28/2025