

Tripp Lite - AGOM7082 : OMNI650LCD

BERGY STAR Unique ID: 2406549 Brand Name: Tripp Lite Model Name: AGOM7082 Model Number: OMNi650LCD Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: ACTIVE OUT OF OUT	Specifications	
Brand Name: Tripp Lite Model Name: AGOM7082 Model Number: OMNI650LCD Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: ACUTE Power Rating Minimum Configuration (W): APPAPER POWER RATING MINIMUM ACONFIGURATION (W): APPAPER POWER RATING MINIMUM CONFIGURATION (W): APPAPER OUTP LOWER POWER POW	-	
Model Name: AGOM7082 Model Number: OMNI650LCD Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (W): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Frequency (Hz): 60-60 Test Output Voltage (V rms): 120 Test Input Frequency (Hz): 60-60 Test Output Voltage (V rms): 120	•	
Model Number: OMNI650LCD Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Apparent Output Power Rating Minimum Configuration (VA): In Interactive Topology (ac): Line Interactive (VI) Application: Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V rms): 15-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		**
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 115-120 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 80-60 Rated Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Nowloular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Model Name:	AGOM7082
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Robert Minimum Son Width (mm): Son Width (mm): Son Width (mm): Bate Total Number of Outlets: No Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): Robert Rating Minimum Robert Robert Robert Input Robert Input Voltage (V): Robert Input Voltage (V): Robert Robert Robert Robert Input Voltage (V): Robert Robert Robert Robert Robert Input Voltage (V): Robert Ro	Model Number:	OMNI650LCD
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Interactive (V) Race Interactiv	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer, Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rate Input Frequency (Hz): Rate Input	Minimum Configuration Tested Model Number:	AGOM7082
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: Nommal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Active Output Power Rating Minimum Configuration (W):	350
Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Charactristic (ac): No Number of Normal Modes: No Number of Normal Modes: Voltage Independent Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Apparent Output Power Rating Minimum Configuration (VA):	650
Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Application:	Consumer,Commercial
Rated Output Voltage (V): 115-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Modes Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Voltage (V):	115-120
Height (mm): 300 Width (mm): 93 Depth (mm): 184 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Rated Output Frequency (Hz):	60-60
Width (mm): Pepth (mm): 184 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Output Voltage (V): 184 Voltage Independent Voltage Independent Voltage Independent 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Rack Mountable:	No
Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage Independent Voltage Independent Nomal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Height (mm):	300
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Width (mm):	93
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Output Voltage (V): 4 Voltage Independent Voltage Independent 120 Test Output Voltage (V): 120	Depth (mm):	184
Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Total Number of Outlets:	8
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Battery Backup and Surge Protected Outlets:	4
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Surge Protected Only Outlets:	4
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Default Normal Mode (ac):	Voltage Independent
Test Output Voltage (V): 120	Test Input Voltage (V rms):	120
, ,	Test Input Frequency (Hz):	60
Test Output Frequency (Hz): 60	Test Output Voltage (V):	120
	Test Output Frequency (Hz):	60

Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): Efficiency at 25% Load Min Config Lowest Dependency (ac): Efficiency at 50% Load Min Config Lowest Dependency (ac): 98.0 Efficiency at 75% Load Min Config Lowest Dependency (ac):
Dependency (ac): Efficiency at 50% Load Min Config Lowest Dependency (ac): 98.0
Dependency (ac):
Fff.:
Efficiency at 75% Load Min Config Lowest Dependency (ac): 98.8
Efficiency at 100% Load Min Config Lowest Dependency (ac): 98.8
Weighted Efficiency Calc Min Config Lowest 98.4 Dependency:
Efficiency (%): 98.4
Modular UPS Module Tested Model Number: N/A
Energy Storage Mechanism: Battery
Energy Storage System Technology: Valve Regulated Lead-acid Battery
Energy Storage System Configuration: Integral
Energy Storage System Removable to Another No Room:
Energy Storage System Runtime at 100% Load (min.):
Energy Storage System Runtime at 50% Load (min.): 12
Energy Storage System Warranty (yrs): 3
Energy Storage System Information URL: N/A
Battery Recycling URL: http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available: USB Port
Communication Protocols: None
Manufacturer Take Back Program: Yes
Manufacturer Take Back Program:YesManufacturer Take Back Program URL:http://www.tripplite.com/en/support/recycling-program.cfm
-
Manufacturer Take Back Program URL: http://www.tripplite.com/en/support/recycling-program.cfm Model Web Page URL: https://www.tripplite.com/omnismart-lcd-120v-650va-350w-line-
Manufacturer Take Back Program URL: http://www.tripplite.com/en/support/recycling-program.cfm Model Web Page URL: https://www.tripplite.com/omnismart-lcd-120v-650va-350w-line-interactive-ups-tower-lcd-display-usb-port~omni650lcd
Manufacturer Take Back Program URL: http://www.tripplite.com/en/support/recycling-program.cfm https://www.tripplite.com/omnismart-lcd-120v-650va-350w-line-interactive-ups-tower-lcd-display-usb-port~omni650lcd Test Method Guidelines: N/A
Manufacturer Take Back Program URL: http://www.tripplite.com/en/support/recycling-program.cfm https://www.tripplite.com/omnismart-lcd-120v-650va-350w-line-interactive-ups-tower-lcd-display-usb-port~omni650lcd Test Method Guidelines: N/A Date Available on Market: 2022-09-01

Captured On: 04/28/2025