

amazonbasics - S175UC: ABMT1000

Specifications ENERGY STAR Unique ID: 2507615 Brand Name: amazonbasics Model Name: S175UC Model Number: ABMT1000 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: 510 Configuration (W): Assignment of Maximum Configuration Tested Model Number: 510 Active Output Power Rating Minimum S175UC Maximum Configuration Tested Model Number: 510 Active Output Power Rating Minimum S175UC Maximum Configuration Tested Model Number: 660 Configuration (W): 5175UC Maximum Configuration (W): 5175UC Active Output Power Rating Minimum Configuration (W): 510Upt Output Output Power Rating Minimum Configuration (W): 510Upt Output Outp		
Brand Name: amazonbasics Model Name: S175UC Model Number: ABMT1000 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: CP850AVRLCDa Active Output Power Rating Minimum Configuration (W): 510 Apparent Output Power Rating Minimum Configuration (VA): 850 Maximum Configuration Tested Model Number: S175UC Maximum Configuration (W): 660 Configuration (W): Line Interactive Topology (ac): Line Interactive (VI) Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 299 Depth (mm): 259 Normal Mode(s) Input Dependency Voltage Independent Characteristic (ac): No Modular UPS: No Modular UPS:	Specifications	
Model Name: S175UC Model Number: ABMT1000 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: CP850AVRLCDa Active Output Power Rating Minimum Configuration (W): 510 Apparent Output Power Rating Minimum Configuration Tested Model Number: S175UC Maximum Configuration Tested Model Number: 660 Active Output Power Rating Maximum Configuration (W): 660 Topology (ac): Line Interactive Topology (ac): Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Voltage Independent Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Ind	ENERGY STAR Unique ID:	2507615
Model Number: ABMT1000 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: 510 Active Output Power Rating Minimum Configuration (W): 850 Apparent Output Power Rating Minimum Configuration (VA): 850 Maximum Configuration Tested Model Number: 660 Active Output Power Rating Maximum Configuration (W): 1150 Active Output Power Rating Maximum Configuration (W): 1160 Application: Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V rms): 120-120 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): No Nomber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Brand Name:	amazonbasics
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Apparent Output Power Rating Minimum Configuration (VA): Maximum Configuration Tested Model Number: Active Output Power Rating Maximum Configuration (W): Active Output Power Rating Maximum Configuration (W): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): Rated Output Frequency (Hz): Ack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120 Test Untput Frequency (Hz): 60 Test Output Voltage (V): 120	Model Name:	S175UC
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (VA): Maximum Configuration Tested Model Number: Active Output Power Rating Maximum Configuration (VA): Maximum Configuration Tested Model Number: Active Output Power Rating Maximum Configuration (W): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): No Height (mm): 229 Width (mm): 99 Depth (mm): Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Voltage (V): 120 Test Untput Voltage (V): 120 Test Untput Voltage (V): 120 Test Untput Voltage (V): 120 Test Output Voltage (V): 120	Model Number:	ABMT1000
Number:Active Output Power Rating Minimum Configuration (W):510Apparent Output Power Rating Minimum Configuration (VA):850Maximum Configuration Tested Model Number:\$175UCActive Output Power Rating Maximum Configuration (W):660Topology (ac):Line InteractiveTopology and Product Type Combined:ac Line Interactive (VI)Application:Consumer,CommercialRated Input Voltage (V rms):120-120Rated Input Frequency (Hz):60-60Rated Output Voltage (V):120-120Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):229Width (mm):99Depth (mm):259Normal Mode(s) Input Dependency Characteristic (ac):NoNormal Mode(s) Input Dependency Characteristic (ac):NoModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage IndependentTest Input Voltage (V):120Test Input Frequency (Hz):60Test Input Frequency (Hz):60Test Output Voltage (V):120	Power Conversion Mechanism:	Static
Configuration (W):\$50Apparent Output Power Rating Minimum Configuration (VA):\$175UCMaximum Configuration Tested Model Number:\$175UCActive Output Power Rating Maximum Configuration (W):\$660Topology (ac):Line InteractiveTopology and Product Type Combined:ac Line Interactive (VI)Application:Consumer, CommercialRated Input Voltage (V rms):120-120Rated Input Frequency (Hz):60-60Rated Output Voltage (V):120-120Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):229Width (mm):99Depth (mm):259Normal Mode(s) Input Dependency Characteristic (ac):Voltage IndependentModular UPS:NoNounber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage IndependentTest Input Voltage (V):120Test Input Voltage (V):120	_	CP850AVRLCDa
Configuration (VA): Maximum Configuration Tested Model Number: Active Output Power Rating Maximum Configuration (W): Topology (ac): Topology and Product Type Combined:		510
Number: Active Output Power Rating Maximum Configuration (W): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		850
Configuration (W): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer,Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	_	S175UC
Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120 Consumer, Commercial ac Line Interactive (VI) Application: Applica		660
Application: Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Voltage (V): 120	Application:	Consumer,Commercial
Rated Output Voltage (V): Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): Rack Mountable: No Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Rated Input Frequency (Hz):	60-60
Rack Mountable: Height (mm): 229 Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Rated Output Voltage (V):	120-120
Height (mm): Width (mm): 99 Depth (mm): 259 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Output Voltage (V): 229 Voltage Independent Voltage Independent 120 Test Output Voltage (V): 120	Rated Output Frequency (Hz):	60-60
Width (mm): Depth (mm): Solve the properties of Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): Test Output Voltage (V): 120	Rack Mountable:	No
Depth (mm): Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): Test Output Voltage (V): 259 Voltage Independent Voltage Independent 120 Test Output Voltage (V): 120	Height (mm):	229
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Voltage Independent Test Input Voltage (V rms): 120 Test Output Voltage (V): 120	Width (mm):	99
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Depth (mm):	259
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): Test Input Frequency (Hz): 60 Test Output Voltage (V): 120		Voltage Independent
Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60 Test Output Voltage (V): 120	Default Normal Mode (ac):	Voltage Independent
Test Output Voltage (V): 120	Test Input Voltage (V rms):	120
	Test Input Frequency (Hz):	60
Test Output Frequency (Hz): 60	Test Output Voltage (V):	120
	Test Output Frequency (Hz):	60

Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	2.9
Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.6
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.7
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.8
Weighted Efficiency Calc Min Config Lowest Dependency:	98.7
Total Input Power in W at 0% Load Max Config Lowest Dependency (ac):	2.72
Efficiency at 25% Load Max Config Lowest Dependency (ac):	98.2
Efficiency at 50% Load Max Config Lowest Dependency (ac):	98.7
Efficiency at 75% Load Max Config Lowest Dependency (ac):	98.9
Efficiency at 100% Load Max Config Lowest Dependency (ac):	98.8
Weighted Efficiency Calc Max Config Lowest Dependency:	98.8
Efficiency (%):	98.7
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	2
Energy Storage System Runtime at 50% Load (min.):	9
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Network Connections Available:	USB Port
Communication Protocols:	Other
Communication Protocol Other:	HID
Manufacturer Take Back Program:	Yes
Model Web Page URL:	https://www.cyberpowersystems.com/product/ups/cp1000avrlcd/
Test Method Guidelines:	N/A
Date Available on Market:	2018-12-31
Date Certified:	2023-05-29
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Captured On: 04/25/2025