



ENERGY STAR CERTIFIED

# Uninterruptible Power Supplies

## EATON TRIPP LITE SERIES, TRIPP.LITE, EATON - SMART1500LCDXNC : AG-07BF

### Specifications

|   |  |
|---|--|
| <b>ENERGY STAR Unique ID:</b>                                   | 3629737                                    |
| <b>Brand Name:</b>  | EATON TRIPP LITE SERIES, TRIPP.LITE, EATON |
| <b>Model Name:</b>  | SMART1500LCDXNC                            |
| <b>Model Number:</b>  | AG-07BF                                    |
| <b>Power Conversion Mechanism:</b>                              | Static                                     |
| <b>Minimum Configuration Tested Model Number:</b>               | AG-07BF                                    |
| <b>Active Output Power Rating Minimum Configuration (W):</b>    | 1050                                       |
| <b>Apparent Output Power Rating Minimum Configuration (VA):</b> | 1440                                       |
| <b>Topology (ac):</b>   | Line Interactive                           |
| <b>Topology and Product Type Combined:</b>                      | ac Line Interactive (VI)                   |
| <b>Application:</b>   | Data Center,Consumer,Commercial            |
| <b>Rated Input Voltage (V rms):</b>                             | 120-120                                    |
| <b>Rated Input Frequency (Hz):</b>                              | 50-60                                      |
| <b>Rated Output Voltage (V):</b>                                | 120-120                                    |
| <b>Rated Output Frequency (Hz):</b>                             | 50-60                                      |
| <b>Rack Mountable:</b>  | Yes  |
| <b>Rack Mount Height (U):</b>                                   | 2  |
| <b>Height (mm):</b>   | 87   |
| <b>Width (mm):</b>  | 438  |
| <b>Depth (mm):</b>  | 280  |
| <b>Total Number of Outlets:</b>                                 | 10   |
| <b>Number of Battery Backup and Surge Protected Outlets:</b>    | 10   |
| <b>Number of Surge Protected Only Outlets:</b>                  | 0  |
| <b>Normal Mode(s) Input Dependency Characteristic (ac):</b>     | Voltage Independent                        |
| <b>Modular UPS:</b>   | No   |
| <b>Number of Normal Modes:</b>                                  | Single-normal-mode                         |
| <b>Default Normal Mode (ac):</b>                                | Voltage Independent                        |
| <b>Test Input Voltage (V rms):</b>                              | 120  |
| <b>Test Input Frequency (Hz):</b>                               | 60   |

|   |   |
|---|---|
| <b>Test Output Voltage (V):</b>                                   | 120   |
| <b>Test Output Frequency (Hz):</b>                                | 60  |
| <b>Efficiency at 25% Load Min Config Lowest Dependency (ac):</b>  | 98.4  |
| <b>Efficiency at 50% Load Min Config Lowest Dependency (ac):</b>  | 98.9  |
| <b>Efficiency at 75% Load Min Config Lowest Dependency (ac):</b>  | 99.0  |
| <b>Efficiency at 100% Load Min Config Lowest Dependency (ac):</b> | 98.9  |
| <b>Weighted Efficiency Calc Min Config Lowest Dependency:</b>     | 98.9  |
| <b>Efficiency (%):</b>  | 98.9  |
| <b>Modular UPS Module Tested Model Number:</b>                    | N/A   |
| <b>Energy Storage Mechanism:</b>                                  | Battery   |
| <b>Energy Storage System Technology:</b>                          | Valve Regulated Lead-acid Battery   |
| <b>Energy Storage System Configuration:</b>                       | Integral  |
| <b>Energy Storage System Removable to Another Room:</b>           | N/A   |
| <b>Energy Storage System Runtime at 100% Load (min.):</b>         | 2   |
| <b>Energy Storage System Runtime at 50% Load (min.):</b>          | 7   |
| <b>Energy Storage System Warranty (yrs):</b>                      | 1   |
| <b>Energy Storage System Information URL:</b>                     | <a href="https://qr.eaton.com/?c=SMART1500LCDXNC">https://qr.eaton.com/?c=SMART1500LCDXNC</a>                             |
| <b>Battery Recycling URL:</b>                                     | <a href="https://tripplite.eaton.com/support/recycling-program">https://tripplite.eaton.com/support/recycling-program</a> |
| <b>Network Connections Available:</b>                             | Ethernet,USB Port   |
| <b>Communication Protocols:</b>                                   | Other   |
| <b>Communication Protocol Other:</b>                              | USB CLI (USB Port), MQTT (Ethernet)   |
| <b>Manufacturer Take Back Program:</b>                            | Yes   |
| <b>Manufacturer Take Back Program URL:</b>                        | <a href="https://tripplite.eaton.com/support/recycling-program">https://tripplite.eaton.com/support/recycling-program</a> |
| <b>Model Web Page URL:</b>  | <a href="https://qr.eaton.com/?c=SMART1500LCDXNC">https://qr.eaton.com/?c=SMART1500LCDXNC</a>                             |
| <b>Test Method Guidelines:</b>                                    | N/A   |
| <b>Date Available on Market:</b>                                  | 2024-10-30  |
| <b>Date Certified:</b>  | 2024-09-29  |
| <b>Markets:</b>   | United States, Canada   |
| <b>ENERGY STAR Certified:</b>                                     | Yes   |

**Captured On:**  
04/25/2025