

EATON TRIPP LITE SERIES, TRIPP.LITE, EATON - SMART750PSRTNC : AG-07C0

Specifications ENERGY STAR Unique ID: 3890949 Brand Name: EATON TRIPP LITE SERIES, TRIPPLITE, EATON Model Name: SMART750PSRTNC Model Number: AG-07C0 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-07C0 Active Output Power Rating Minimum Configuration (W): A75 Apparent Output Power Rating Minimum Configuration (WA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Chartes Input Frequency (Hz): No Normal Mode(ac): Voltage Input Dependency Chartes Input Frequency (Hz): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Frequency (Hz): 50-60 Fast Input Frequency (Hz): No Test Input Frequency (Hz): No Test Input Frequency (Hz): No		
Brand Name: EATON TRIPP LITE SERIES, TRIPP.LITE, EATON Model Name: SMART750PSRTNC Model Number: AG-07C0 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: ACtive Output Power Rating Minimum Configuration (W): AF5 Active Output Power Rating Minimum Configuration (W): Topology (ac): Line Interactive Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Specifications	
Model Name: SMART750PSRTNC Model Number: AG-07C0 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-07C0 Active Output Power Rating Minimum Configuration (W): 475 Apparent Output Power Rating Minimum Configuration (VA): 750 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Output Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 37 Midth (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-n	ENERGY STAR Unique ID:	3890949
Model Number: AG-07C0 Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: AG-07C0 Active Output Power Rating Minimum Configuration (W): 475 Apparent Output Power Rating Minimum Configuration (VA): 750 Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Inp	Brand Name:	EATON TRIPP LITE SERIES, TRIPP.LITE, EATON
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Model Name:	SMART750PSRTNC
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Application: Rated Input Voltage (V): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rack Mountable: Rack Mountable: Rack Mount Height (U): Height (mm): 330 Depth (mm): 315 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Model Number:	AG-07C0
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Application: Application: Application: Ated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): Acted Output Voltage (V): Ated Output Voltage (V): Acted Output Voltage (V): Acted Output Voltage (V): Acted Output Frequency (Hz): Acted Output Fre	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Muntable: Rack Mountable: Rack Mountable: Rack Mount Height (U): Height (mm): Width (mm): 330 Depth (mm): 315 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	_	AG-07C0
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Frequency (Hz): So-60 Rated Output Voltage (V): Rated Output Frequency (Hz): So-60 Rack Mountable: Yes Rack Mountable: Yes Rack Mount Height (U): Beight (mm): So-60 Rack Mount Height (U): Beight (mm): Brack Mount Height (U): Brack Mount Height (U): Brack Mount Meight (U): Brack Mount Mei	•	475
Topology and Product Type Combined: Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120		750
Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 50-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 50-60 Rack Mountable: Yes Rack Mount Height (U): 2 Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Noundlar UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Rated Input Frequency (Hz):	50-60
Rack Mount Height (U): Rack Mount Height (U): Height (mm): Width (mm): Sand Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Rated Output Voltage (V):	120-120
Rack Mount Height (U): Height (mm): 87 Width (mm): 330 Depth (mm): 315 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Number of Surge Protected Only Outlets: Voltage Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 120	Rated Output Frequency (Hz):	50-60
Height (mm): Width (mm): 330 Depth (mm): 315 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Rack Mountable:	Yes
Width (mm): 330 Depth (mm): 315 Total Number of Outlets: 8 Number of Battery Backup and Surge Protected Outlets: 0 Number of Surge Protected Only Outlets: 0 Normal Mode(s) Input Dependency Characteristic (ac): No Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Rack Mount Height (U):	2
Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120	Height (mm):	87
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 8 No Voltage Independent Voltage Independent	Width (mm):	330
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent Voltage Independent	Depth (mm):	315
Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 120	Total Number of Outlets:	8
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Voltage Independent Test Input Voltage (V rms): Voltage Independent 120		8
Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): 120	Number of Surge Protected Only Outlets:	0
Number of Normal Modes: Default Normal Mode (ac): Voltage Independent Test Input Voltage (V rms): 120		Voltage Independent
Default Normal Mode (ac): Voltage Independent 120	Modular UPS:	No
Test Input Voltage (V rms): 120	Number of Normal Modes:	Single-normal-mode
	Default Normal Mode (ac):	Voltage Independent
Test Input Frequency (Hz):	Test Input Voltage (V rms):	120
rest inpat i requeito (112).	Test Input Frequency (Hz):	60

Test Output Voltage (V): 12	20
Test Output Frequency (Hz): 60)
Efficiency at 25% Load Min Config Lowest 97. Dependency (ac):	7.0
Efficiency at 50% Load Min Config Lowest 98. Dependency (ac):	3.3
Efficiency at 75% Load Min Config Lowest 98. Dependency (ac):	3.7
Efficiency at 100% Load Min Config Lowest 98. Dependency (ac):	3.8
Weighted Efficiency Calc Min Config Lowest 98. Dependency:	3.6
Efficiency (%):	3.6
Modular UPS Module Tested Model Number: N/A	/A
Energy Storage Mechanism: Ba	attery
Energy Storage System Technology: Va	alve Regulated Lead-acid Battery
Energy Storage System Configuration: Int	tegral
Energy Storage System Removable to Another N/Room:	/A
Energy Storage System Runtime at 100% Load 2 (min.):	
Energy Storage System Runtime at 50% Load 8 (min.):	
Energy Storage System Warranty (yrs): 1	
Energy Storage System Information URL: htt	tps://qr.eaton.com/?c=SMART750PSRTNC
Battery Recycling URL: htt	tps://tripplite.eaton.com/support/recycling-program
Network Connections Available: Eth	hernet,USB Port
Communication Protocols: Oth	ther
Communication Protocol Other: US	SB CLI (USB Port), MQTT (Ethernet)
Manufacturer Take Back Program: Yes	es
Manufacturer Take Back Program URL: htt	tps://tripplite.eaton.com/support/recycling-program
Model Web Page URL: htt	tps://qr.eaton.com/?c=SMART750PSRTNC
Test Method Guidelines: N/A	
	/A
Date Available on Market: 20	/A 025-02-24
Date Certified: 20	025-02-24

Captured On: 04/28/2025